



SPOOLS, SPOOL CABLE SEALS & REDUCER BUSHINGS

INDUSTRIAL SPOOL CABLE SEALS

STANDARD SPOOLS	
Ordering No.	Upper Case Well
7E0PS3	7"
10E0PSA	10"
12E0PSA	12"
14E0PSA	14"

Ordering No.	Cable Range	Cable Size	Cable Material
UG193	.125-.187	#14,12	4 wire Twstd Plastic
UG192	.187-.312	#10,8,6 #14, 12, 10	4 wire Twstd Plastic 4 wire Twstd Rubber
UG255	.312-.437	#8, 6, 4, 3	4 wire Twstd Rubber
UG355	.37-.50	#2	4 wire Twstd Rubber

SILENT CHECK VALVE SPOOLS	
Ordering No.	Upper Case Well
7E2PS3	7"
10E2PSA	10"

FLOWING WELL SILENT CHECK VALVE SPOOLS	
Ordering No.	Upper Case Well
7E2PS3F	7"
10E2PSF	10"

FLOWING WELL SPOOLS	
Ordering No.	Upper Case Well
7E0PS3F	7"
10E0PSF	10"
12E0PSF	12"
14E0PSF	14"

REDUCER BUSHINGS	
Ordering No.	Size
PC335 Galv.	3" x 2"
UK254x29 Galv.	4" x 2"
G18.4x3 Galv.	4" x 3"
UL168 Galv.	6" x 3"
G18.6x4 Galv.	6" x 4"
UL254 Galv.	6" x 5"
UQ66 Galv.	8" x 6"

FLANGED DISCHARGE KITS		Flange discharge kits convert discharge on 6 x 7 through 16 x 18 (Standard Model) Industrial Pittless Units from threaded to flanged. (Each kit includes 150 lb. raised flange). Swagged nipples also available.
Ordering No.	Discharge Size	
3UC	3"	
4UG	4"	
6UJ	6"	
8UM	8"	

CABLE SEALS For use with 10", 12" & 14" Monitor Premium Watertight caps.

Model	Cable Range	Cable Size	Cable Material
53UK4	.125-.187 O.D.	#14, 12	4 wire Twstd Plastic
54UK4	.187-.312 O.D.	#10, 8, 6 #14, 12, 10	4 wire Twstd Plastic 4 wire Twstd Rubber
55UK4	.312-.437 O.D.	#8, 6, 4, 3	4 wire Twstd Rubber
56UK4	.437-.500 O.D.	#2	4 wire Twstd Rubber
57UK4	.500-.625 O.D.	#1, 1/0, 2/0	4 wire Twstd Rubber
58UK4	.625-.750 O.D.	#3/0, 4/0	4 wire Twstd Rubber

FOR FURTHER INFORMATION ON ORDER NUMBERS SEE UNIT SPECIFICATIONS