



O-RING SELECTION GUIDE FOR FULL PITLESS UNITS

Model <i>(Well Size X Upper Case Size)</i>	O-Ring Part No.	Inside Diameter		Thickness	
2 x 3	NA115	2.350	.018	.210	.005
3 x 4	NB15	3.400	.015	.210	.005
4 x 5	UB15	4.10	.028	.210	.005
4 x 8	UB15	4.10	.028	.210	.005
5 x 6	NC15	5.10	.037	.275	.006
5 x 8	NC15	5.10	.037	.275	.006
5.6 x 7	UC15	5.975	.037	.275	.006
6 x 7	UC15	5.975	.037	.275	.006
6.6 x 7	UC15	5.975	.037	.275	.006
6 x 8	UH15	6.975	.040	.275	.006
7 x 8	UH15	6.975	.040	.275	.006
8 x 10	UG15	8.475	.055	.275	.006
10 x 12	UJ15	10.550	.030	.375	.010
12 x 14	UK15	11.540	.030	.375	.010
14 x 16	UL15	13.110	.030	.500	.020
16 x 18	UM15	14.900	.030	.625	.022
18 x 20	UN15	16.840	.030	.625	.022
20 x 22	UQ15A	18.550	.030	.625	.022
24 x 26	UR15A	22.430	.030	.625	.022
26 x 28	US15A	24.600	.030	.625	.022